







Max 300 mm



As from 440 kgs



600 litres



HIGH PRESSURE CLEANING

URBANJET

TAKING DRAIN CLEARANCE TO THE NEXT LEVEL

LIGHTWEIGHT

The new light weight UrbanJet is designed to fit most compact 3.5T vans such as the VW Transporter, Ford Transit, Vauxhall Movano, MB Vito or similar sized vans. The new UrbanJet is ideally suited for unblocking of house connections and work in domestic and light commercial areas. The UrbanJet is also available with an industrial, water cooled diesel or petrol engine to service pipes up to 300 mm.

EVERYTHING YOU NEED

The UrbanJet is supplied as a complete package including hydraulically driven high pressure hose reel with 60 metres MaxFlow lightweight jetting hose and filling reel with 35 metres of NW19 hose. The optionally included 5 or 7 channel radio remote control allows single man operation and allows the user to control the pump (on/off) and engine revs and emergency stop.

The run dry function for low water pump protection has an override facility allowing the operator to use the hydraulic system to retrieve the hose from the drain. The UrbanJet is available with several different tank configurations for optimum flexibility.

eCONTROL+ INTERFACE

Despite its affordable price the new UrbanJet is fitted with our award winning eControl⁺ user interface with LCD display. It includes many useful features and provides a full machine status at a glance. The eControl+ system also provides the user with machine error information for quick fault diagnostics.





- Lightweight to fit most popular and compact 3.5t + vehicles
- eControl+ control panel with machine status indicators
- Hydraulically driven high pressure hose reel as standard
- Optionally equipped with radio remote control for single man operation

Romed	

RioMote radio remote control optionally available



Compact built, leaving space for camera and tools

O	M 700	
Operating range	Max 300 mm	
Engine	Kubota diesel D1105 (18.5 kW/25 HP) or Kubota petrol industrial WG972 (24 kW/32 HP)	
Pump	Kubota diesel D1105	
Rioned/Speck	200 bar / 45 lpm 140 bar / 60 lpm	3000 psi / 10 gpr 2000 psi / 13 gpn
	Kubota petrol indus	trial WG972
	200 bar / 55 lpm 140 bar / 70 lpm	3000 psi / 12 gpn 2000 psi/ 15 gpm
Pump protection	Run dry protection with overrun possibility	
Pressure regulator	Type Speck with automatic bypass	
Water tank	2 x 300 litres (600 litres total)	
Fuel tank	30 litres	
Filling reel	35 metres filling hose	
HP hose	60 metres NW13 (1/2")	
HP hose reel	Fixed hose reel, hydraulically operated	
Control	Rioned eControl ⁺ with LCD display, warning lights, hour counter and service interval warning	
Weight	As from 440 kgs	
Dimensions (LxWxH)	1305 x 1240 x 1195 mm	
Nozzles	2 x 1/2" (1 open, 1 blind)	
Color	Blue covers, black metal frame	
OPTIONS		
Remote control	RioMote 5 or 7 channel radio remote control (gas regulation, pump on/off, emergency stop)	
RioPulse Pulsator	Pump adjusment to send water in pulses through the hose	
Anti-freeze tank	30 litres anti-freeze tank mounted to protect HP circuit. Drain valve mounted on heat exchanger	
Extra water tanks	2x 400 or 4x 300 litres litres water tanks instead of 2 x 300 litres	
Extra hose length	80 metres NW 13 (1/2") MaxFlow hose instead of 60 metres	
Ventury tank filling system	Suction device to fill up the tank with water form natural sources	
Mechanic freewheel HP hose reel	RioFree mechanical freewheel at the hose reel for coiling off without any resistance	
Hydrant connection	Supply line with hydrant connection for fast filling of the water tank	
Accessories	Spraygun and lance	